Series		Model Name	Dimension (DxWxH mm)	Motherborad support	Drive Bays Support	Expansion Slots	I/O Ports	Max. Radiator Support	Pre-installed Fan(s)	Fan Support	Max. CPU Cooler Height	Max. VGA Card Length	Dust Filtration
Performance		P110 Luce*	489 x 230 x 518	ATX,Micro-ATX,ITX	3.5" x 6 (convertible with 4 x 2.5"SSD) 2.5" x 2	8(horizontal)+ 2(vertical)	POWER, USB3.0 x 2, HDMI, MIC/AUDIO, RGB LED CONTROL	Front: 360mm Top: 280mm (up to 55mm thickness with fan) Rear: 120mm	Front: 1 x 120mm Rear: 1 x 120mm	Front: 3x120mm or 2x140mm Top: 2x120mm or 2x140mm Rear: 1x120mm	165mm	≤ 390mm (vertical) ≤ 390mm (horizontal)	Top/Front/Bottom
		P110 Silent	489 x 230 x 518	ATX,Micro-ATX,ITX	3.5" x 6 (convertible with 4 x 2.5"SSD) 2.5" x 2	8(horizontal)+ 2(vertical)	POWER, USB3.0 x 2, HDMI, MIC/AUDIO	Front: 360mm Top: 280mm (up to 55mm thickness with fan) Rear: 120mm	Front: 1 x 120mm Rear: 1 x 120mm	Front: 3x120mm or 2x140mm Top: 2x120mm or 2x140mm Rear: 1x120mm	165mm	≤ 390mm (vertical) ≤ 390mm (horizontal)	Top/Front/Bottom
		P8*	443 x 210 x 470	ATX,Micro-ATX,ITX	3.5"/2.5" x 2 2.5" x 4	7	POWER, USB3.0 x 2 RESET, MIC/AUDIO	Front: 360mm Top: 240mm limited (up to 55mm thickness with fan) Rear: 120mm	Front: 2 x White LED 120mm fans Rear: 1 x White LED 120mm fan	Front: 3x120mm or 2x140mm Top: 3x120mm or 2x140mm Rear: 1x120mm	165mm	≤ 390mm	Top/Front/Bottom
		P7 Window	445x 210 x 470	ATX,Micro-ATX,Mini-ITX	3.5"/2.5" x 2 2.5" x 2	7	Power, USB3.0 x 2, MIC/AUDIO(HD), Reset	Front: 360mm (up to 55mm thickness with fan) Rear: 120mm	Rear: 1 x 120mm	Front: 3x120mm or 2x140mm Rear: 1x120mm	165mm	≤ 390mm	Front/Bottom
		P7 Silent	445x 210 x 470	ATX,Micro-ATX,Mini-ITX	5.25" x 1 3.5"/2.5" x 2 2.5" x 2	7	Power, USB3.0 x 2, MIC/AUDIO(HD), Reset	Front: 280mm limited (up to 55mm thickness with fan) Rear: 120mm	Front: 1 x 120mm Rear: 1 x 120mm	Front: 2x120mm or 2x140mm Rear: 1x120mm	165mm	≤ 390mm	Front/Bottom
		P6*	470x 200 x 405	Micro-ATX,ITX	3.5"/2.5" x 2 2.5" x 4	4	Power, USB3.0 x 2, MIC/AUDIO(HD), Reset	Front: 240mm (Up to 55mm thickness with fan) Rear: 120mm	Rear: 1 x White LED 120mm fan	Front: 2x120mm/2x140mm Top: 3x120mm/2x140mm Rear: 1x120mm	160mm	≤ 390mm	Top/Front/Bottom
Gaming		DF500 RGB*	470x 200 x 480	ATX,Micro-ATX,Mini-ITX	3.5"/2.5" x 2 2.5" x 4	7	USB3.0 x 2, MIC/AUDIO(HD), Power, RGB LED CONTROL	Front: 360mm (Up to 55mm thickness with fan) Rear: 120mm	Front: 3 x RGB LED 120mm fan	Front: 3x120mm/2x140mm Top: 3x120mm/2x140mm Rear: 1x120mm	165mm	≤ 380mm	Top/Front/Bottom
		DF500	470x 200 x 480	ATX,Micro-ATX,Mini-ITX	3.5"/2.5" x 2 2.5" x 4	7	Power, USB3.0 x 2, MIC/AUDIO(HD), Reset	Front: 360mm (Up to 55mm thickness with fan) Rear: 120mm	Rear: 1 x 120mm	Front: 3x120mm/2x140mm Top: 3x120mm/2x140mm Rear: 1x120mm	165mm	≤ 380mm	Top/Front/Bottom
SI		VSK 3000 Elite	410x 180 x 373	Micro-ATX,Mini-ITX	5.25" x 1 3.5" x 4 (convertible with 1 x 2.5"SSD) 2.5" x 1	4	Power, USB3.0 x 2, MIC/AUDIO(HD), Reset	Rear: 120mm	Rear: 1 x 120mm	Front: 1x120mm or 1x80mm Rear: 1x120mm or 1x80mm Left Panel: 2x120mm	160mm	≤ 335mm	N/A

* TEMPERED GLASS SIDE PANEL